

AQUA GROUP

TEXMO®

Pumps you can rely on



SINGLE PHASE SELF PRIMING MINI MONOBLOCK PUMPS

IS: 8472



CM/L:3431446

AQUA MINI SERIES





Pumps you can rely on

SINGLE PHASE SELF PRIMING MINI MONOBLOCK PUMPS

AQUA MINI SERIES

"TEXMO" Single Phase Self Priming Mini-Monoblock pumps are the products from AQUA GROUP Asia's only totally integrated pump manufacturing group of companies. AQUA GROUP'S pumps are synonymous with Quality and Reliability. The AQUA MINI SERIES pumps are rugged in construction and efficient. They are manufactured with stringent quality control at all stages to provide higher efficiency and reliability.

Salient Features

- Sturdy Die cast Aluminium Motor Frame
- Portable and light weight in construction
- Easy to install and need simple maintenance
- Capacitor placed inside the terminal box
- Better Aesthetic look with Powder coated finish
- Performance Certified by BIS with ISI marking

Motor

- Rugged Single phase TEFC motor construction
- Aluminium Die-cast motor frame
- Suitable for 200-240V Single Phase, 50Hz power supply
- In-built Thermal Overload Protector (T.O.P)
- Permanent -split capacitor design for better reliability
- Double shielded Ball Bearings

Applications

- Domestic water supply
- Water transfer from under ground sump to overhead tanks in Residential Houses and Apartments
- Domestic Pressure Boosting
- High pressure curing water supply at construction sites
- Lawn and Garden Watering

Pump

- Rigid cast iron Pump Casing
- Forged Brass impeller
- Corrosion resistant Stainless Steel Shaft
- High quality Carbon Vs Ceramic Mechanical Seal
- In-built Non Return Valve (N.R.V)

PERFORMANCE DATA

Model	Rating HP/kW	Pipe Size (mm)	TOTAL HEAD IN METERS							
			6	9	12	15	18	21	24	30
			DISCHARGE IN LITRES PER HOUR							
AQUAMINI-2	0.5 / 0.37	25 X 25	2550	2350	2100	1900	1700	1500	1300	950
AQUAMINI-2 JUNIOR	0.5 / 0.37	25 X 25	1950	1700	1450	1200	950	700	500	—

NOTE:

- 1, The above performance is based on rated voltage and rated frequency and as per the relevant indian standard tolerances.
- 2, Total head includes Static suction, Static delivery and friction losses in pipes and bends.
- 3, The maximum static suction head is upto 6 meters at mean sea level.
- 4, The self priming time depends upon static suction, Installation conditions and the usage of the pumps.
- 5, Due to continuous efforts for improving performance value, information furnished is subject to change without notice

Warranty: All products carry a 12 months warranty from the date of purchase against manufacturing defects.

AQUA GROUP

AQUASUB ENGINEERING AQUAPUMP INDUSTRIES

TUDIYALUR POST, COIMBATORE-641 034. INDIA
Email: marketing@aquagroup.in
Website: www.aquagroup.in

Authorised Sales / Service Dealers: